

# QUV Accelerated Weathering Tester



## Overview

Sunlight, heat, and moisture cause millions of dollars of material damage every year. The QUV® accelerated weathering tester exposes materials to alternating cycles of UV light and moisture at controlled, elevated temperatures. In a few days or weeks, the QUV tester can reproduce the damage that occurs over months or years outdoors. With thousands of testers in service worldwide, the QUV tester is the world's most widely used weathering tester.

## Features

QUV testers are available in four different models: QUV/basic, QUV/se, QUV/spray, and QUV/cw. Each air-cooled tester features Q-Lab's renowned reliability and ease of maintenance. All testers have standard datalogging via ethernet and/or USB, a variety of standard sample holders, automatic fault recognition and alarms, automatic shut-down timer, and a remarkably simple user interface available in eight languages.

|  | QUV/basic                       | QUV/se | QUV/spray | QUV/cw |
|--|---------------------------------|--------|-----------|--------|
| <b>Specimen Orientation</b>                                  | 75° (measured from horizontal)  |        |           |        |
| <b>UV Fluorescent Lamps - 40W</b>                            | Quantity: 8 (T12 x 121 cm long) |        |           |        |
| <b>SOLAR EYE® Irradiance Control<sup>2</sup></b>             | —                               | ●      | ●         | ●      |
| <b>Dual Full-Color Touch-Screen Displays</b>                 | —                               | ●      | ●         | ●      |
| <b>Water Spray</b>   | —                               | —      | ●         | —      |
| <b>Condensation</b>  | ●                               | ●      | ●         | ●      |
| <b>Insulated Black Panel (IBP) Temp. Control<sup>3</sup></b> | ●                               | ●      | ●         | ●      |
| <b>Adjustable 3D Specimen Holder Boxes<sup>1</sup></b>       | ●                               | ●      | ●         | ●      |
| <b>Space Saver Frame for Stacking<sup>4</sup></b>            | ●                               | ●      | ●         | ●      |
| <b>Water Repurification System</b>                           | —                               | —      | ●         | —      |

● Standard Feature    ● Optional Feature

1 See LU-8001 for more information on other standard and custom specimen mounting holder options.

2 See L-3000 for information about SOLAR EYE Irradiance Control calibration using the Universal Calibrator System.

3 Black Panel (BP) temperature control is standard. IBP control recommended for use with plastic specimens and/or 3D specimen holder boxes.

4 See LU-0820 for more information on space saver frames.

## Lamps & Irradiance Control

The SOLAR EYE® irradiance control system (used in all models except QUV/basic) continuously monitors and precisely maintains irradiance by adjusting power to the lamps. Irradiance control is very important because changes in light intensity may affect both speed and type of material degradation. The QUV/basic model relies on lamp rotation to approximate controlled irradiance levels.

Models with irradiance control feature programmable setpoints. For example, with UVA-340 lamps, an irradiance of 0.89 W/m<sup>2</sup>/nm@340nm is a good match with noon summer sunlight. For faster results, the QUV tester can operate at about double the irradiance of noon summer sunlight. See below for some common set points and LU-8160 for more information about selecting lamps for your application.

|                           | UVA-340 | UVA-340+ | UVA-351 | UVB-313EL | UVB-313EL+ | QFS-40 | Cool White |
|---------------------------|---------|----------|---------|-----------|------------|--------|------------|
| <b>Minimum Irradiance</b> | 0.20    | 0.70     | 0.20    | 0.20      | 0.20       | 0.20   | 2,000 lux  |
| <b>Typical Irradiance</b> | 0.89    | 0.89     | 0.76    | 0.71      | 0.71       | 0.48   | 6,000 lux  |
| <b>High Irradiance</b>    | 1.55    | 1.55     | 1.25    | 1.23      | 1.55       | 0.86   | 20,000 lux |
| <b>Maximum Irradiance</b> |         | 1.70     |         |           | 1.70       |        |            |

1: Values above are in units of W/m<sup>2</sup>/nm unless otherwise indicated.

2: All lamps in testers equipped with SOLAR EYE irradiance control are warranted for 8,000 hours at Typical Irradiance; UVA-340+ and UVB-313EL+ are also warranted for 1,500 hours at High Irradiance and 750 hours at Maximum Irradiance. Italicized values above are not warranted.

## Irradiance Calibrations

The QUV SOLAR EYE irradiance control system and on-board sensors can be calibrated quickly and inexpensively using the Universal Calibrator (UC) system. Disposable, ISO 17025-accredited smart sensors can be connected directly to the dual touchscreen display, dramatically simplifying the calibration process and lowers operating costs for users (see L-3000 for more information).



## QUV Tester Operating Specifications:

| Models   | QUV/basic  | QUV/se   | QUV/spray  | QUV/cw   |
|--|--|--|--|--|
| <b>Black Panel Temp (°C)</b><br>Light Cycle Temp. <sup>1</sup><br>Condensation Cycle Temp. | 45-80<br>40-60   | 45-80<br>40-60   | 45-80<br>40-60   | 35-80<br>— <sup>2</sup>  |
| <b>Specimen Exposure Area</b>  | 20 x 50 cm<br>(2x front side)<br>20 x 108 cm<br>(1x rear side)<br>4160 cm <sup>2</sup> total | 20 x 50 cm<br>(2x each side)<br>4000 cm <sup>2</sup> total         | 20 x 50 cm<br>(2x each side)<br>4000 cm <sup>2</sup> total         | 20 x 50 cm<br>(2x each side)<br>4000 cm <sup>2</sup> total         |
| <b>Specimen Capacity</b> <sup>3</sup>  | 50 Specimens<br>(75 x 150 mm)  | 48 Specimens<br>(75 x 150 mm)                                      | 48 Specimens<br>(75 x 150 mm)                                      | 48 Specimens<br>(75 x 150 mm)                                      |
| <b>Inlet Water Pressure</b>  | 0.2-5.5 bar<br>(2-80 psi)  | 0.2-5.5 bar<br>(2-80 psi)  | 2.8-5.5 bar<br>(40-80 psi) <sup>4</sup>                            | 0.2-5.5 bar<br>(2-80 psi)  |
| <b>Inlet Water Purity</b> <sup>5</sup>   | Tap Water  | Tap Water  | > 200 kΩ-cm<br>< 5 μS/cm<br>< 2.5 ppm TDS<br>6-8 pH                | Tap Water <sup>2</sup>   |
| <b>Water Consumption</b> <sup>6</sup><br>Condensation<br>Spray                             | 5 liters/day<br>—  | 5 liters/day<br>—  | 5 liters/day<br>7 liters/minute                                    | 5 liters/day <sup>2</sup><br>—                                     |
| <b>External Dimensions</b><br>(w x h x d)  | 137 x 135 x 53 cm<br>(54 x 53 x 21 in)   |  |  |  |
| <b>Weight</b> <sup>7</sup>   | 136 kg (300 lbs)   |  |  |  |
| <b>Electrical Requirements</b> <sup>8</sup>  | 120V ± 10%, 1-Φ,<br>60 Hz, 14A<br>230V ± 10%, 1-Φ,<br>50/60 Hz, 7A                           | 120V ± 10%, 1-Φ,<br>60 Hz, 16A<br>230V ± 10%, 1-Φ,<br>50/60 Hz, 8A | 120V ± 10%, 1-Φ,<br>60 Hz, 16A<br>230V ± 10%, 1-Φ,<br>50/60 Hz, 8A | 120V ± 10%, 1-Φ,<br>60 Hz, 16A<br>230V ± 10%, 1-Φ,<br>50/60 Hz, 8A |

1 Minimum and maximum black panel temperatures are dependent on irradiance settings and ambient temperatures.

2 The QUV/cw model is able to perform condensation cycles; however, this is not usually applicable for testing indoor materials.

3 Other specimen sizes and shapes (including three-dimensional specimens) are readily accommodated in standard or custom specimen holders (see LU-8001).

4 Optional booster pump (X-10570-K) is available.

5 Water purity requirements can be met by most reverse osmosis, deionization, or distillation systems.

6 Water consumption values are dependent upon test and lab conditions. Values shown are maximum for many common standards. To reduce water consumption during spray cycles, consider an optional water repurification system (see LW-6048 for more information).

7 Actual shipping weights will be higher and depend upon whether the shipment is domestic, ocean, or air.

8 Transformer kits available for 100V (part number V-149-K-INST) or 200V (part number V-149.1-K-INST) operation.

## Warranty

The QUV accelerated weathering tester is guaranteed against defects in workmanship or materials for one year. Liability is limited to replacing or repairing any part or parts which are defective in materials or workmanship and are returned to our factory, shipping costs prepaid. Liability in all events is limited to the purchase price paid. Damage due to accident or abuse is not covered. Labor and travel costs are not covered. Q-Lab Corporation makes no other warranties, including implied warranties of merchantability or fitness for a particular purpose, except as may be expressly provided by Q-Lab Corporation in writing. Q-Lab Corporation shall not be liable for any incidental, consequential, special, or contingent damages arising out of the sale or use of any product.



For sales, technical, or repair support, please visit:

**Q-Lab.com/support**

Westlake, Ohio USA • Homestead, Florida USA • Buckeye, Arizona USA  
Bolton, England • Saarbrücken, Germany • Shanghai, China